



WHITE

BLACK

Black

Charcoal

Brown

White

4500/4501

Premium Commercial / Industrial Steel Panel

Constructed of top quality materials with pebble grain embossed finish, designed for each application, and engineered for years of dependable operation.

- ◆ 25 gauge steel
- ◆ 1.0 mil paint with 4 color options
- ◆ R-value 6.85 *4501 Feature
- ◆ Vinyl interior skin *4501 Feature

*Colors may vary from actual product

4500/4501

Non-insulated Insulated

Premium Commercial/Industrial Steel Panel

25 GAUGE

Features



25 GAUGE STEEL

Panels are pebble grain embossed with two deep ribs and six small grooves. Sections are 2" thick.



ROLLED SAFETY EDGES ON SECTION JOINTS

Interior flange of panel has a hemmed edge.



17 GAUGE HOT DIPPED GALVANIZED STEEL STILES

Open sides of center and end stiles have rolled edges for safety and added strength.



STILES ATTACHED WITH RIVETS

Stiles are mechanically fastened and adhesive bonded to panel to act as an integral structure of the section.



TONGUE AND GROOVE MEETING RAILS

For superior strength and better sealing against wind, rain, and snow.



RIGID ALUMINUM RETAINER WITH WEATHERSTRIP

Provides added strength while securing replaceable U-type bottom astragal weatherstrip to help keep the elements out.



GLAZING

Options of 24" x 6" or 24" x 12" windows are available. Optional Series 8000 Full View sections can be substituted for steel sections up to 18' 2".



WIND LOAD

Consult factory for available wind load rated options.



6.85

INSULATION

Model 4501 doors are insulated with polystyrene insulation. Interior face of insulation is covered with a vinyl protective skin. Insulation R-value is 6.85. [*4501 Feature](#)

Size Options


WIDTH:

UP TO 9'2"	<input type="checkbox"/>	<input type="checkbox"/>							
9'3" TO 12'2"	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>						
12'3" TO 17'2"	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>					
17'3" TO 18'2"	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>				
18'3" TO 22'2"	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>			

HEIGHT: 21", 24"

*Contact your distributor for additional heights.

Paint System




1.0 MIL PAINT SYSTEM

Includes .25 mil rust inhibiting primer and .75 mil exterior top coat that resists fading and chalking, while providing consistent color from panel to panel and more durability.

- 1 Paint - .75 MIL
- 2 Primer - .25 MIL
- 3 Steel
- 4 Primer - .2 MIL
- 5 Paint - .3 MIL

Construction



- 1 Tongue and groove meeting rails
- 2 Hemmed interior rails
- 3 2" thick section
- 4 Heavy duty galvanized steel end and center stiles; fastened and bonded as integral structures of the section
- 5 CFC free expanded polystyrene insulation with vinyl backing ([standard on 4501](#))
- 6 Deep ribbed steel panel, galvanized and painted
- 7 Rolled edge on open side of stiles
- 8 Replaceable U-Type vinyl bottom weatherstrip
- 9 Extruded aluminum weatherstrip retainer

*This image is showing 4501

Window & Glass Options



See website for glass options

doorLink
MANUFACTURING, INC.*



5700 NW 39th St, Riverside, MO 64150
816-474-3900 / sales@doorlinkmfg.com

© doorLink Manufacturing, Inc.