## **Raised Ranch Panel**

24 GAUGE





WHITE

# 490/491 **Raised Ranch Panel**

Constructed of top quality materials, highly detailed raised ranch panel, deep woodgrain texture, and two coat prefinished paint system all combine to enhance the beauty of your home.

- 24 gauge steel
- 1.0 mil paint with 8 color options
- **6 window options**
- R-value 6.85 \*491 Feature
- Vinyl interior skin \*491 Feature



MANUFACTURING, INC.

## 490/491 | Raised Ranch Panel 24 GAUGE

#### **Features**

#### **24 GAUGE STEEL** 24

Hot dipped galvanized steel construction with hemmed inside return rail provides superior strength and durability.

#### **ROLLED SAFETY EDGES ON SECTION JOINTS**

Eliminates sharp edges, and provides extra strength.



#### **19 GAUGE HOT DIPPED GALVANIZED STILES**

Heavy duty metal stiles give strong rigid support for all hinges, rollers, and operator attachment.



#### **STILES ATTACHED WITH RIVETS**

Provides superior strength when compared to common sheet metal joining methods.



#### **TONGUE AND GROOVE MEETING RAILS**

For superior strength and better sealing against wind, rain, and snow.



#### **RIGID ALUMINUM RETAINER WITH** WEATHERSTRIP

Provides added strength while securing replaceable U-type bottom astragal weatherstrip to help keep the elements out.



#### **R-VALUE 6.85**

Enhances your home's energy savings, makes your door operation quieter, and reduces exterior noise in your garage. \*491 Feature



#### HIGH IMPACT PLASTIC BACK COVER

Protects the insulation, and enhances the interior look of your garage door. \*491 Feature




### **CFC FREE EXPANDED POLYSTYRENE**

Environmentally friendly insulation that will not degrade with vibration or time. \*491 Feature

#### Size Options







15', 16'

17', 18'

20', 22'



\*Contact your distributor for additional heights.





# **Window Options**



#### **Window Glass Options**

See website for glass options

#### Paint System



#### **1.0 MIL PAINT SYSTEM**

Includes .25 mil rust inhibiting primer and .75 mil exterior top coat that resists fading and chalking, while providing consistent color from panel to panel and more durability.


- Paint .75 MIL 1
  - Primer .25 MIL
  - Steel

2

3

- 4 Primer - .2 MIL
- 5 Paint - .3 MIL

## Construction



DASMA

#### Tongue and groove meeting rails 1

- 2 Hemmed interior rails
- 2" thick section 3
- 4 19 gauge hot dipped galvanized steel stiles
- CFC free expanded polystyrene insulation with 5 vinyl backing (standard on 491)
- Replaceable U-Type vinyl bottom weatherstrip 6
- Extruded aluminum weatherstrip retainer 7

\*This image is showing 491

5700 NW 39th St, Riverside, MO 64150 816-474-3900 / sales@doorlinkmfg.com © doorLink Manufacturing, Inc.



\*Not all glazing options may be available from all distributors. No glazing on 18" sections